
## Installation Instructions for Big Daddy Fishing Rod Racks

## **Included Hardware**

- Rod Racks (2)
- Screws (12)
- Wall Anchors (12)

## **Tools Needed (Not Supplied)**

- Level
- · Pen, Pencil, or Sharp Object
- Drill (with appropriate bit size for wall anchors)
- Phillips Screwdriver or Drill Driver
- Hammer



## Steps for Installation

- **1. Prepare Your Workspace:** Lay out all included hardware and tools on a flat surface to ensure everything is organized and accessible.
- **2. Choose a Location:** Decide where to mount the rod rack—on the ceiling for overhead storage or on a wall, either horizontally or vertically. Use a level to ensure the rack is aligned to your preference.
- **3. Mark the Anchor Holes:** Hold the first rod rack in the desired position and use a pen, pencil, or sharp object to mark the six anchor hole locations through the base of the rack.
- **4. Drill Holes for Wall Anchors:** Use a drill to create holes at the marked locations, ensuring each hole matches the size of the provided wall anchors in both diameter and depth.
- **5. Insert Wall Anchors:** Gently tap the wall anchors into the drilled holes using a hammer until they are flush with the surface.
- **6. Secure the First Rod Rack:** Hold the rod rack in place and drive the screws through the six holes in the rack base, securing it to the wall or ceiling using a Phillips screwdriver or drill driver.
- **7. Position the Second Rod Rack:** Insert a fishing pole into the installed rod rack and use the opposite end of the pole as a guide to position the second rod rack accurately.
- **8. Install the Second Rod Rack:** Repeat the process from step 3 to step 6 to secure the second rod rack in the desired position.
- **9. Expand with Additional Racks (Optional):** For added capacity, connect additional racks by joining their interlocking ends to expand storage as needed.

Your rod racks are now securely installed and ready for use!

